NSN 5925-00-923-2117

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-923-2117

Overall Length:
6.500 inches
Overall Height:
2.750 inches
Overall Width:
3.500 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.188 inches
Pole Quantity:
2
Arc Quenching Method:
Deion
Mounting Facility Type And Quantity:
3 unthreaded hole
Maximum Continuous Load Current Rating Per Pole:
50.0 amperes ac all locations and 50.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
480.0 ac all locations and 250.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
10000.0 ac all locations and 10000.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Actuator Function:
Trip w/separate reset
Thread Size:
0.164 inches
Trip Release Duty Cycle:

Trip Delay Time In Seconds Per Rated Continuous Current:

Continuous all locations

200.000 at 125 pct all locations and 30.000 at 200 pct all locations and 10.000 at 300 pct all locations

NSN 5925-00-923-2117

Circuit Breaker - Page 2 of 2



Trip Release Ambient Tempurature Rating: 25.0 degrees celsius all locations Special Features: Mtg holes irregularly spaced Thread Series Designator: Un Terminal Type And Quantity: 4 screw Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A030a0