

View Online at <https://aerobasegroup.com/nsn/5925-00-923-2117>

Overall Length:

6.500 inches

Overall Height:

2.750 inches

Overall Width:

3.500 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.188 inches

Pole Quantity:

2

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

3 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations and 50.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Actuator Function:

Trip w/separate reset

Thread Size:

0.164 inches

Trip Release Duty Cycle:

Continuous all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

200.000 at 125 pct all locations and 30.000 at 200 pct all locations and 10.000 at 300 pct all locations

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Special Features:

Mtg holes irregularly spaced

Thread Series Designator:

Un

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0