

View Online at <https://aerobasegroup.com/nsn/5925-00-923-2118>

**Overall Length:**

6.500 inches

**Overall Height:**

2.750 inches

**Overall Width:**

3.500 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Deion

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

70.0 amperes ac all locations and 70.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac all locations and 10000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Actuator Function:**

Trip w/separate reset

**Thread Size:**

0.164 inches

**Trip Release Duty Cycle:**

Continuous all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

160.000 at 125 pct all locations and 22.000 at 200 pct all locations and 5.000 at 300 pct all locations

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Special Features:**

Mtg holes irregularly spaced

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0