NSN 5925-00-924-9596

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-924-9596

Body Style: Single pole type **Body Length:** Between 3.667 inches and 3.793 inches **Body Width:** Between 0.937 inches and 1.063 inches Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: Between 3.050 inches and 3.070 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.740 inches and 2.760 inches **Fragility Factor:** Moderately rugged **Boss Height:** Between 0.097 inches and 0.223 inches **Mounting Surface To Terminal End Distance:** Between 2.960 inches and 3.150 inches **Pole Quantity:** 1 Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 100.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

NSN 5925-00-924-9596

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.500 at 200 pct single location and 50.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Vibration resistant and shock resistant and salt spray proof and humidity resistant

Unpackaged Unit Weight:

0.530 pounds

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0