# NSN 5925-00-925-5097

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-925-5097

# Thread Pitch Diameters:

+0.3503/+0.3537 inches

#### Body Style:

Multipole-single actuator type

#### **Bushing Length:**

Between 0.365 inches and 0.390 inches

#### Body Length:

1.562 inches

#### **Body Width:**

1.937 inches

#### **Case Material:**

#### Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.865 inches and 0.885 inches

#### Center To Center Distance Between Terminals Parallel To Width:

Between 0.594 inches and 0.656 inches

#### **Fragility Factor:**

Moderately rugged

#### Mounting Surface To Terminal End Distance:

1.828 inches

# Pole Quantity:

3

#### Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

#### Storage Type:

General purpose warehouse

#### **Special Handling Feature:**

Magnetic

Thready Qty Per Inch (tpi):

32

#### Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac third location

#### **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Magnetic-hydraulic all locations

#### **Trip Release Characteristic:**

Time delay all locations

# NSN 5925-00-925-5097

Circuit Breaker - Page 2 of 2



# Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

130.0 all locations

# **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

### Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 200 pct all locations and 5.000 at 200 pct all locations

# Inclosure Protection Type For Which Designed:

Fungus resistant and hermetically sealed and moisture resistant

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

4.500 ounces

### **Precious Material And Location:**

Contact surfacescpl-1bjab5.0 silver

#### **Precious Material:**

Silver

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire hook

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0