NSN 5925-00-925-5097

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-925-5097

Thread Pitch Diameters:
+0.3503/+0.3537 inches
Body Style:
Multipole-single actuator type
Bushing Length:
Between 0.365 inches and 0.390 inches
Body Length:
1.562 inches
Body Width:
1.937 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
Between 0.865 inches and 0.885 inches
Center To Center Distance Between Terminals Parallel To Width:
Between 0.594 inches and 0.656 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.828 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac third location
5.0 amperes ac third location
5.0 amperes ac third location Operating Voltage Type And Rating Per Pole In Volts:
5.0 amperes ac third location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations
5.0 amperes ac third location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
5.0 amperes ac third location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations
5.0 amperes ac third location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations Circuit Protection Type:
5.0 amperes ac third location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations Circuit Protection Type: Overcurrent all locations

Time delay all locations

NSN 5925-00-925-5097

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
130.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
1.000 at 200 pct all locations and 5.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and hermetically sealed and moisture resistant
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
4.500 ounces
Precious Material And Location:
Contact surfacescpl-1bjab5.0 silver
Precious Material:
Silver
Thread Series Designator:
Unef
Terminal Type And Quantity:
6 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0