NSN 5925-00-928-1587

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-928-1587

Body Style:

Multipole-single actuator type

Body Length:

10.120 inches

Body Width:

4.120 inches

Body Height:

3.810 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

8.380 inches

Center To Center Distance Between Terminals Parallel To Width:

1.380 inches

Unthreaded Mounting Hole Diameter:

0.245 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

7.750 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.380 inches

Boss Height:

0.500 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

200.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

NSN 5925-00-928-1587

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

2 alarm

Internal Trip Release Configuration:

Shunt trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

95.000 at 200 pct all locations and 260.000 at 200 pct all locations

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

Switch Terminal Type:

Wire lead

Switch Current Rating And Type In Amps:

5.0 ac

Switch Voltage Rating And Type In Volts:

240.0 ac

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 screw and 2 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0