NSN 5925-00-928-8243

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-928-8243

Body Style:

Multipole-multiple actuator type

Body Length:

2.500 inches

Body Width:

3.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.938 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.140 inches

Mounting Surface To Terminal End Distance:

2.611 inches

Pole Quantity:

4

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

8 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

NSN 5925-00-928-8243

Circuit Breaker - Page 2 of 2



Trip Release Characteristic: Time delay all locations Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 150.0 all locations **Reset Method:** Manual Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 4 toggle Actuator Function: Trip-reset **Actuator Position Designation:** At each pole **External Actuator Linkage Arrangement:** One, two, three, and four linked Internal Trip Release Configuration: Series trip all locations **Thread Size:** 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 0.230 at 200 pct all locations and 0.650 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Fungus resistant and moisture resistant Frequency In Hertz: 400.0 all locations **Thread Series Designator:** Unc **Terminal Type And Quantity:** 8 threaded stud Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0