

View Online at <https://aerobasegroup.com/nsn/5925-00-930-2265>

**Body Style:**

Multipole-single actuator type

**Body Length:**

Between 15.470 inches and 15.530 inches

**Body Width:**

Between 8.220 inches and 8.280 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

Between 11.590 inches and 11.650 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 2.720 inches and 2.780 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.340 inches and 0.400 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 14.220 inches and 14.280 inches

**Switch Contact Arrangement:**

Double pole, double throw

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.720 inches and 2.780 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.350 inches and 0.410 inches

**Mounting Surface To Terminal End Distance:**

Between 10.970 inches and 11.030 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

700.0 amperes ac all locations and 700.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations and 125.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

25000.0 ac all locations and 65000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Auxiliary Switch Function And Quantity:**

1 control

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+2100.0/+7000.0 ac all locations and +2100.0/+7000.0 dc all locations

**Switch Location And Position Designation:**

Internal at pole three

**Inclosure Protection Type For Which Designed:**

Hermetically sealed and weatherproof

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Switch Terminal Type:**

Wire lead

**Switch Current Rating And Type In Amps:**

6.0 ac and 0.5 dc

**Switch Voltage Rating And Type In Volts:**

600.0 ac and 125.0 dc

**Frequency In Hertz:**

60.0 all locations

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0