NSN 5925-00-934-2648

Circuit Breaker - Page 1 of 2

Trip free



View Online at https://aerobasegroup.com/nsn/5925-00-934-2648

Thread Pitch Diameters:
+0.3503/+0.3537 inches
Body Style:
Single pole type
Bushing Length:
0.380 inches
Body Length:
1.500 inches
Body Width:
0.625 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.875 inches
Mounting Surface To Terminal End Distance:
1.605 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
1 threaded bushing
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
1.5 amperes ac single location and 1.5 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac single location and 50.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac single location and 1000.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Magnetic single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:

NSN 5925-00-934-2648 Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.090 at 200 pct single location and 0.600 at 200 pct single location
Inclosure Protection Type For Which Designed:
Shockproof and vibrationproof and hermetically sealed
Frequency In Hertz:
400.0 single location
Test Data Document:
19315-1945824 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unef
Terminal Type And Quantity:
2 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0