

View Online at <https://aerobasegroup.com/nsn/5925-00-936-3909>

Body Style:

Single pole type

Bushing Length:

0.395 inches

Body Length:

0.750 inches

Body Width:

0.434 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.500 inches

Mounting Surface To Terminal End Distance:

1.670 inches

Pole Quantity:

1

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location and 5.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 24.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

30.0 ac single location and 30.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.438 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct single location and 40.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Shockproof

Trip Release Ambient Temperature Rating:

77.0 degrees fahrenheit single location

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Un

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0