NSN 5925-00-936-3933



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-936-3933 **Body Style:** Multipole-single actuator type **Body Length:** 3.000 inches **Body Width:** 2.234 inches **Body Height:** 2.312 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Boss Height:** 0.250 inches **Pole Quantity: Mounting Facility Type And Quantity:** 6 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 60.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Actuator Function: Trip-reset

NSN 5925-00-936-3933

Circuit Breaker - Page 2 of 2

No Fiig: A030a0



Actuator Position Designation: At pole two **Trip Delay Time In Seconds Per Rated Continuous Current:** 25.000 at 200 pct all locations and 80.000 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Fungus resistant **Trip Release Ambient Tempurature Rating:** 40.0 degrees celsius all locations **Special Features:** Use mounting kit sk5668 when replacing a q1b360 breaker. Frequency In Hertz: 60.0 all locations **Terminal Type And Quantity:** 3 clip and 3 compression Shelf Life: N/a **Unit Of Measure: Demilitarization:**