

View Online at <https://aerobasegroup.com/nsn/5925-00-938-3447>

Body Style:

Rectangular dimensional envelope

Overall Length:

6.500 inches

Overall Height:

4.125 inches

Overall Width:

4.875 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

100.0 amperes ac all locations and 100.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+600.0/+1300.0 ac all locations

Thread Size:

0.190 inches

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant and shock resistant

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Special Features:

Ent2732 is a factory installed shunt trip unit with auxiliary switch; rated voltage 120 vdc; rated current 100 amps

Frequency In Hertz:

60.0 all locations

Precious Material And Location:

Main contacts silver

Precious Material:

Silver

Thread Series Designator:

Unf

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0