NSN 5925-00-941-8158

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-941-8158

view Online at https://aerobasegroup.com/hsn/5925-00-941-6156
Body Style:
Rectangular dimensional envelope
Overall Length:
9.000 inches
Overall Height:
1.000 inches
Overall Width:
4.812 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
6 unthreaded hole
Storage Type:
Unimproved open
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
400.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+1900.0/+3500.0 ac all locations
Trip Delay Time In Seconds Per Rated Continuous Current:

110.000 at 200 pct all locations

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

NSN 5925-00-941-8158

Circuit Breaker Tripper - Page 2 of 2



Frequency I	In Hertz:
-------------	-----------

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A030a0