

View Online at <https://aerobasegroup.com/nsn/5925-00-941-8194>

Body Style:

Single pole type

Bushing Length:

0.390 inches

Body Length:

1.140 inches

Body Width:

0.570 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.890 inches

Mounting Surface To Terminal End Distance:

2.260 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

27

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location and 15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location and 24.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Reset

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

7.000 at 300 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and hermetically sealed

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0