

View Online at <https://aerobasegroup.com/nsn/5925-00-945-1118>

Body Style:

Rectangular dimensional envelope

Overall Length:

6.000 inches

Overall Height:

3.000 inches

Overall Width:

4.410 inches

Case Material:

Plastic

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

70.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

25.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Thread Size:

0.164 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

8.000 at 300 pct all locations and 20.000 at 300 pct all locations and 3.600 at 400 pct all locations and 8.000 at 400 pct all locations

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Nuclear Hardness Critical Feature:

Hardened

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0