NSN 5925-00-949-1215

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-949-1215

Body Style:

Multipole-single actuator type

Bushing Length:

Between 0.365 inches and 0.390 inches

Body Length:

1.562 inches

Body Width:

1.281 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.594 inches and 0.656 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.594 inches and 0.656 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.828 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

2.0 amperes ac first location2.5 amperes dc second location

Operating Voltage Type And Rating Per Pole In Volts:

28.0 dc second location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 ac first location750.0 dc second location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

130.0 all locations

NSN 5925-00-949-1215 Circuit Breaker - Page 2 of 2

Reset Method:ManualMain Contact Tripping Mechanism Type:Trip freeManual Actuator Type And Quantity:1 toggleActuator Function:Trip-resetActuator Position Designation:Between pole one and twoInternal Trip Release Configuration:Series trip all locationsThread Size:0.375 inchesTrip Delay Time In Seconds Per Rated Continuous Current:1.000 at 200 pct all locations and
Main Contact Tripping Mechanism Type:Trip freeManual Actuator Type And Quantity:1 toggleActuator Function:Trip-resetActuator Position Designation:Between pole one and twoInternal Trip Release Configuration:Series trip all locationsThread Size:0.375 inchesTrip Delay Time In Seconds Per Rated Continuous Current:
Trip free Manual Actuator Type And Quantity: 1 toggle Actuator Function: Trip-reset Actuator Position Designation: Between pole one and two Internal Trip Release Configuration: Series trip all locations Thread Size: 0.375 inches
Manual Actuator Type And Quantity:1 toggleActuator Function:Trip-resetActuator Position Designation:Between pole one and twoInternal Trip Release Configuration:Series trip all locationsThread Size:0.375 inchesTrip Delay Time In Seconds Per Rated Continuous Current:
1 toggle Actuator Function: Trip-reset Actuator Position Designation: Between pole one and two Internal Trip Release Configuration: Series trip all locations Thread Size: 0.375 inches Trip Delay Time In Seconds Per Rated Continuous Current:
Actuator Function:Trip-resetActuator Position Designation:Between pole one and twoInternal Trip Release Configuration:Series trip all locationsThread Size:0.375 inchesTrip Delay Time In Seconds Per Rated Continuous Current:
Trip-reset Actuator Position Designation: Between pole one and two Internal Trip Release Configuration: Series trip all locations Thread Size: 0.375 inches Trip Delay Time In Seconds Per Rated Continuous Current:
Actuator Position Designation: Between pole one and two Internal Trip Release Configuration: Series trip all locations Thread Size: 0.375 inches Trip Delay Time In Seconds Per Rated Continuous Current:
Between pole one and two Internal Trip Release Configuration: Series trip all locations Thread Size: 0.375 inches Trip Delay Time In Seconds Per Rated Continuous Current:
Internal Trip Release Configuration: Series trip all locations Thread Size: 0.375 inches Trip Delay Time In Seconds Per Rated Continuous Current:
Series trip all locations Thread Size: 0.375 inches Trip Delay Time In Seconds Per Rated Continuous Current:
Thread Size: 0.375 inches Trip Delay Time In Seconds Per Rated Continuous Current:
0.375 inches Trip Delay Time In Seconds Per Rated Continuous Current:
Trip Delay Time In Seconds Per Rated Continuous Current:
1.000 at 200 pct all locations and
Inclosure Protection Type For Which Designed:
Hermetically sealed and
Frequency In Hertz:
400.0 first location
Unpackaged Unit Weight:
2.100 ounces
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:
Unit Of Measure:
Unit Of Measure: Demilitarization:
 Demilitarization:
 Demilitarization: No

