

View Online at <https://aerobasegroup.com/nsn/5925-00-956-5715>

**Overall Length:**

9.375 inches

**Overall Height:**

4.125 inches

**Overall Width:**

4.812 inches

**Case Material:**

Plastic

**Pole Quantity:**

3

**Arc Quenching Method:**

Deion

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

15000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

122.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Thread Size:**

0.281 inches

**Trip Release Duty Cycle:**

Continuous all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

40.000 at 150 pct all locations and 220.000 at 150 pct all locations and 16.000 at 200 pct all locations and 45.000 at 200 pct all locations and 5.100 at 300 pct all locations and 10.000 at 300 pct all locations and 2.100 at 500 pct all locations and 4.350 at 500 pct all locations and 0.020 to 1.150 sec at 1150 pct all locations

**Inclosure Protection Type For Which Designed:**

Dustproof

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Special Features:**

Mtg holes on 7.250 in. By 1.375 in. Mtg centers

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0