

View Online at <https://aerobasegroup.com/nsn/5925-00-956-5715>

Overall Length:

9.375 inches

Overall Height:

4.125 inches

Overall Width:

4.812 inches

Case Material:

Plastic

Pole Quantity:

3

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

122.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Thread Size:

0.281 inches

Trip Release Duty Cycle:

Continuous all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

40.000 at 150 pct all locations and 220.000 at 150 pct all locations and 16.000 at 200 pct all locations and 45.000 at 200 pct all locations and 5.100 at 300 pct all locations and 10.000 at 300 pct all locations and 2.100 at 500 pct all locations and 4.350 at 500 pct all locations and 0.020 to 1.150 sec at 1150 pct all locations

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Special Features:

Mtg holes on 7.250 in. By 1.375 in. Mtg centers

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0