

View Online at <https://aerobasegroup.com/nsn/5925-00-957-0467>

Body Style:

Multipole-single actuator type

Body Length:

Between 5.240 inches and 5.260 inches

Body Width:

Between 2.990 inches and 3.010 inches

Body Height:

Between 2.677 inches and 2.697 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 4.349 inches and 4.369 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.974 inches and 0.994 inches

Unthreaded Mounting Hole Diameter:

0.190 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 3.052 inches and 3.072 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.974 inches and 0.994 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.208 inches and 0.228 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole and 4 unthreaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes ac first location 7.5 amperes ac second location

Operating Voltage Type And Rating Per Pole In Volts:

200.0 ac second location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac first location 5000.0 ac second location

Circuit Protection Type:

Overcurrent first locationovercurrent second location

Trip Release Method:

Magnetic-hydraulic first locationmagnetic-hydraulic second location

Trip Release Characteristic:

Time delay first locationtime delay second location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 first location125.0 second location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip first locationseries trip second location

Thread Size:

0.164 inches

Switch Location And Position Designation:

External at pole three

Trip Delay Time In Seconds Per Rated Continuous Current:

30.000 at 200 pct first location and 100.000 at 200 pct first location30.000 at 200 pct second location and 100.000 at 200 pct second location

Inclosure Protection Type For Which Designed:

Dustproof and fungus proof

Switch Terminal Type:

Threaded stud

Special Features:

Pole three is a switch only

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0