

View Online at <https://aerobasegroup.com/nsn/5925-00-957-4774>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

Between 0.365 inches and 0.390 inches

**Body Length:**

1.562 inches

**Body Width:**

1.937 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.865 inches and 0.885 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.594 inches and 0.656 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

1.828 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

230.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

500.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.000 at 150 pct all locations and 8.000 at 150 pct all locations and 1.000 at 200 pct all locations and 3.000 at 200 pct all locations and 0.200 at 300 pct all locations and 0.900 at 300 pct all locations

**Inclosure Protection Type For Which Designed:**

Watertight and dustproof

**Frequency In Hertz:**

400.0 all locations

**Precious Material:**

Silver

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0