## NSN 5925-00-958-8215

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-958-8215

**Body Style:** Multipole-multiple actuator type **Body Length:** 2.520 inches **Body Width:** 2.280 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 1.200 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.810 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Mounting Surface To Terminal End Distance:** 2.010 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 6 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 500.0 milliamperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 208.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

125.0 all locations

## **NSN 5925-00-958-8215** Circuit Breaker - Page 2 of 2



Ultimate Trip Time Per Pole In Seconds:
2.000 all locations and 10.000 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
3 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
4.000 at 200 pct all locations and 9.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0