

View Online at <https://aerobasegroup.com/nsn/5925-00-963-4042>

Overall Length:

2.337 inches

Overall Height:

0.750 inches

Overall Width:

1.094 inches

Case Material:

Plastic

Pole Quantity:

1

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location and 15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

200.0 ac single location and 28.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

116.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

60.000 at 150 pct single location and 900.000 at 150 pct single location and 18.000 at 200 pct single location and 50.000 at 200 pct single location and 6.000 at 300 pct single location and 20.000 at 300 pct single location

Inclsure Protection Type For Which Designed:

Explosion proof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 screw

Specification Data:

36659-613540-1 manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A030a0