NSN 5925-00-964-9654



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-964-9654 **Body Style:** Single pole type **Bushing Length:** 0.380 inches **Body Length:** 1.750 inches **Body Width:** 0.640 inches **Case Material:** Metal **Center To Center Distance Between Terminals Parallel To Length:** Between 0.594 inches and 0.656 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.680 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Storage Type: General purpose warehouse **Special Handling Feature:**

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

7.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

110.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Reset Method:

Manual

NSN 5925-00-964-9654 Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.150 at 200 pct single location and 0.800 at 200 pct single location
Inclosure Protection Type For Which Designed:
Hermetically sealed and shock resistant and vibration resistant and corrosion resistant and moisture resistant
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
2.000 ounces
Thread Series Designator:
Unef
Terminal Type And Quantity:
2 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0