## NSN 5925-00-965-7668



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-965-7668 **Body Style:** Single pole type **Body Length:** 3.875 inches **Body Width:** 0.938 inches **Body Height:** 2.234 inches **Case Material: Plastic Boss Height:** 0.130 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 5000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Instantaneous single location and time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Ultimate Trip Time Per Pole In Seconds:** 1500.000 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 

1 toggle

Actuator Function:

Trip-reset

## **NSN 5925-00-965-7668** Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Trip Delay Time In Seconds Per Rated Continuous Current:
50.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Unpackaged Unit Weight:
5.200 ounces
Terminal Type And Quantity:
1 clip and 1 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0