## NSN 5925-00-965-8496

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-965-8496

Overall Length:
13.093 inches
Overall Height:
9.625 inches
Overall Width:
4.687 inches
Case Material:
Metal
Pole Quantity:
3
Arc Quenching Method:
Deion
Mounting Facility Type And Quantity:
4 unthreaded hole
Maximum Continuous Load Current Rating Per Pole:
30.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
7500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Thread Size:
0.250 inches
Trip Release Duty Cycle:
Continuous all locations
Trip Delay Time In Seconds Per Rated Continuous Current:

30.000 at 150 pct all locations and 240.000 at 150 pct all locations and 3.000 at 500 pct all locations and 5.000 at 500 pct all locations

## NSN 5925-00-965-8496

Circuit Breaker - Page 2 of 2



Trip Release Ambient Tempurature Rating	Trip	Release	Ambient	<b>Tempuratur</b>	e Rating
---	------	---------	---------	-------------------	----------

25.0 degrees celsius all locations

**Special Features:** 

Flush mtd on 11.750 in. By 8.000 in. Mtg centers

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0