NSN 5925-00-965-8497



Circuit Breaker - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5925-00-965-8497
Overall Length:
13.093 inches
Overall Height:
9.625 inches
Overall Width:
6.687 inches
Case Material:
Metal
Pole Quantity:
3
Arc Quenching Method:
Deion
Mounting Facility Type And Quantity:
4 unthreaded hole
Maximum Continuous Load Current Rating Per Pole:
40.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
7500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Thread Size:
0.250 inches
Trip Release Duty Cycle:
Continuous all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
30.000 at 150 pct all locations and 240.000 at 150 pct all locations and 3.000 at 500 pct all locations and 5.000 at 500 pct all locations
Inclosure Protection Type For Which Designed:

Dustproof

NSN 5925-00-965-8497

Circuit Breaker - Page 2 of 2



Trip Release Ambient Tempurature Rating: 25.0 degrees celsius all locations Special Features: Flush mtd on 11.750 in. By 8.000 in. Mtg centers Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: - Demilitarization: No

Fiig: A030a0