

View Online at <https://aerobasegroup.com/nsn/5925-00-969-1450>

Overall Length:

5.000 inches

Overall Height:

5.687 inches

Overall Width:

4.750 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.328 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.375 inches

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac all locations and 25.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac all locations and 125.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations and 5000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Trip Delay Time In Seconds Per Rated Continuous Current:

60.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0