

View Online at <https://aerobasegroup.com/nsn/5925-00-969-3067>

Body Style:

Single pole type

Mounting Slot Width:

0.094 inches

Body Length:

3.500 inches

Body Width:

0.969 inches

Body Height:

2.312 inches

Case Material:

Plastic

Boss Height:

0.188 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 slot

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location and 15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac single location and 125.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location and 2500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Ultimate Trip Time Per Pole In Seconds:

3600.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct single location and 100.000 at 200 pct single location

Trip Release Ambient Temperature Rating:

50.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Terminal Type And Quantity:

1 quick disconnect, male and 1 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0