NSN 5925-00-971-2126

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-971-2126 **Body Style:** Multipole-multiple actuator type **Body Length:** 2.500 inches **Body Width:** 2.250 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 1.938 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.140 inches **Mounting Surface To Terminal End Distance:** 2.609 inches **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 6 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 5.5 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1500.0 ac all locations **Circuit Protection Type:** Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

NSN 5925-00-971-2126Circuit Breaker - Page 2 of 2



| Trip Release Characteristic: |
|--|
| Time delay all locations |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 125.0 all locations |
| Reset Method: |
| Manual |
| Main Contact Tripping Mechanism Type: |
| Nontrip free |
| Manual Actuator Type And Quantity: |
| 3 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At each pole |
| External Actuator Linkage Arrangement: |
| One, two, and three linked |
| Internal Trip Release Configuration: |
| Series trip all locations |
| Thread Size: |
| 0.138 inches |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 2.500 at 200 pct all locations and 9.000 at 200 pct all locations |
| Inclosure Protection Type For Which Designed: |
| Fungus resistant and moisture resistant |
| Frequency In Hertz: |
| 400.0 all locations |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 6 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |