## NSN 5925-00-972-9984

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-972-9984

| Body Style:  |
|--|
| Rectangular dimensional envelope                                       |
| Overall Length:  |
| 17.937 inches  |
| Overall Height:  |
| 6.187 inches   |
| Overall Width:   |
| 9.000 inches   |
| Unthreaded Mounting Hole Diameter:                                     |
| 0.500 inches   |
| Pole Quantity:   |
| 3  |
| Arc Quenching Method:  |
| Air  |
| Mounting Facility Type And Quantity:                                   |
| 2 unthreaded hole  |
| Features Provided:   |
| Adjustable trip release  |
| Cubic Measure:   |
| 998.786 cubic inches   |
| Maximum Continuous Load Current Rating Per Pole:                       |
| 250.0 amperes ac all locations   |
| Operating Voltage Type And Rating Per Pole In Volts:                   |
| 500.0 ac all locations   |
| Circuit Protection Type:   |
| Overcurrent all locations  |
| Trip Release Method:   |
| Thermal-magnetic all locations   |
| Trip Release Characteristic:   |
| Instantaneous all locations  |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 130.0 all locations  |
| Ultimate Trip Time Per Pole In Seconds:                                |
| 3600.000 all locations   |
| Manual Actuator Type And Quantity:                                     |
| 1 toggle   |
| Actuator Function:   |
| Trip-reset   |
| Actuator Position Designation:   |
| At pole two  |
| Adjustable Trip Setting Current Range Per Pole In Amps:                |

+880.0/+1530.0 ac all locations

## NSN 5925-00-972-9984

Circuit Breaker Tripper - Page 2 of 2



| Trip Release Ambient Tempurature Rating: |
|--|
| 50.0 degrees celsius all locations       |
| Frequency In Hertz:                      |
| 60.0 all locations                       |

**Unpackaged Unit Weight:** 

4.500 pounds

**Terminal Type And Quantity:** 

6 compression

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0