NSN 5925-00-972-9984

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-972-9984

Body Style:
Rectangular dimensional envelope
Overall Length:
17.937 inches
Overall Height:
6.187 inches
Overall Width:
9.000 inches
Unthreaded Mounting Hole Diameter:
0.500 inches
Pole Quantity:
3
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole
Features Provided:
Adjustable trip release
Cubic Measure:
998.786 cubic inches
Maximum Continuous Load Current Rating Per Pole:
250.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
130.0 all locations
Ultimate Trip Time Per Pole In Seconds:
3600.000 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:

+880.0/+1530.0 ac all locations

NSN 5925-00-972-9984

Circuit Breaker Tripper - Page 2 of 2



Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations

Unpackaged Unit Weight:

4.500 pounds

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0