

View Online at <https://aerobasegroup.com/nsn/5925-00-973-0776>

Body Style:

Single pole type

Body Length:

6.000 inches

Body Width:

7.500 inches

Body Height:

2.312 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Boss Height:

0.156 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 terminal

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac single location and 20.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location and 250.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 ac single location and 7500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

7.000 at 300 pct single location and 10.000 at 300 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

1 clip and 1 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0