

View Online at <https://aerobasegroup.com/nsn/5925-00-975-0975>

Overall Length:

2.843 inches

Overall Height:

2.921 inches

Overall Width:

0.968 inches

Case Material:

Plastic

Pole Quantity:

1

Arc Quenching Method:

Deion

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Trip Release Duty Cycle:

Continuous single location

Trip Delay Time In Seconds Per Rated Continuous Current:

90.000 at 150 pct single location and 200.000 at 150 pct single location and 30.000 at 200 pct single location and 55.000 at 200 pct single location and 14.000 at 300 pct single location and 26.000 at 300 pct single location and 8.000 at 400 pct single location and 14.000 at 400 pct single location and 5.000 at 500 pct single location and 9.000 at 500 pct single location

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Special Features:

Mounting type is terminal

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

1 screw and 1 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0