

View Online at <https://aerobasegroup.com/nsn/5925-00-977-5843>

**Body Style:**

Multipole-single actuator type

**Overall Height:**

10.032 inches

**Body Length:**

10.156 inches

**Body Width:**

5.000 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

8.750 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.625 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

8.750 inches

**Switch Contact Arrangement:**

Double pole, double throw

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.625 inches

**Boss Height:**

0.188 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded stud

**Thready Qty Per Inch (tpi):**

20

**Maximum Continuous Load Current Rating Per Pole:**

25.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

440.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

100000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip w/separate reset

**Actuator Position Designation:**

At pole two

**Auxiliary Switch Function And Quantity:**

1 control

**Thread Size:**

0.250 inches

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Switch Terminal Type:**

Wire lead

**Switch Current Rating And Type In Amps:**

10.0 ac and 5.0 ac

**Switch Voltage Rating And Type In Volts:**

125.0 ac and 250.0 ac

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0