NSN 5925-00-983-5298

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-983-5298

| view Offilite at https://aerobasegroup.com/hts//0325-00-305-3230 |
|--|
| Body Style: |
| Rectangular dimensional envelope |
| Overall Length: |
| 13.094 inches |
| Overall Height: |
| 4.062 inches |
| Overall Width: |
| 8.125 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.312 inches |
| Fragility Factor: |
| Moderately rugged |
| Pole Quantity: |
| 3 |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Storage Type: |
| General purpose warehouse |
| Maximum Continuous Load Current Rating Per Pole: |
| 350.0 amperes ac all locations |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 600.0 ac all locations |
| Circuit Protection Type: |
| Overcurrent all locations |
| Trip Release Method: |
| Thermal all locations |
| Trip Release Characteristic: |
| Instantaneous all locations and time delay all locations |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 135.0 all locations |
| Internal Trip Release Configuration: |
| Series trip all locations |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 90.000 at 200 pct all locations and 450.000 at 200 pct all locations |
| Trip Release Ambient Tempurature Rating: |
| 40.0 degrees celsius all locations |
| Frequency In Hertz: |
| 60.0 all locations |
| Terminal Type And Quantity: |
| 6 compression |
| Shelf Life: |

N/a

NSN 5925-00-983-5298

Circuit Breaker Tripper - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A030a0