# NSN 5925-00-984-3006

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-984-3006

### **Body Style:**

Multipole-single actuator type

### **Body Length:**

10.138 inches

## Body Width:

5.500 inches

#### **Body Height:**

3.812 inches

#### **Case Material:**

Plastic

### Center To Center Distance Between Terminals Parallel To Length:

### 8.875 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 1.719 inches

**Unthreaded Mounting Hole Diameter:** 

### 0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.437 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.719 inches

### **Fragility Factor:**

Moderately rugged

#### **Boss Height:**

0.500 inches

### Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

### Mounting Facility Type And Quantity:

4 unthreaded hole

### Storage Type:

General purpose warehouse

### Maximum Continuous Load Current Rating Per Pole:

125.0 amperes ac all locations

### **Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations

### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Thermal-magnetic all locations

# NSN 5925-00-984-3006

Circuit Breaker - Page 2 of 2



Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

**Actuator Function:** 

Trip-reset

**Actuator Position Designation:** 

At pole two

Trip Delay Time In Seconds Per Rated Continuous Current:

170.000 at 200 pct all locations and 460.000 at 200 pct all locations

## Inclosure Protection Type For Which Designed:

General purpose

**Trip Release Ambient Tempurature Rating:** 

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

**Terminal Type And Quantity:** 

6 screw

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0