

View Online at <https://aerobasegroup.com/nsn/5925-00-984-6125>

Body Style:

Multipole-multiple actuator type

Body Length:

Between 3.709 inches and 3.729 inches

Body Width:

Between 3.042 inches and 3.062 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 3.053 inches and 3.073 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 1.021 inches and 1.041 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.740 inches and 2.760 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.021 inches and 1.041 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.146 inches and 0.166 inches

Mounting Surface To Terminal End Distance:

3.239 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

416.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1300.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.300 at 200 pct all locations and 1.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

1.850 pounds

Precious Material And Location:

Terminal surfaces silver

Precious Material:

Silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0