NSN 5925-00-984-9123

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-984-9123

Body Style:

Multipole-single actuator type

Body Length:

6.062 inches

Body Width:

4.219 inches

Body Height:

3.406 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.125 inches

Center To Center Distance Between Terminals Parallel To Width:

1.375 inches

Unthreaded Mounting Hole Diameter:

0.225 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

Boss Height:

0.250 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations and 20.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

NSN 5925-00-984-9123 Circuit Breaker - Page 2 of 2



anual	
ain Contact Tripping Mechanism Type:	
ip free	
anual Actuator Type And Quantity:	
oggle	
ctuator Function:	
ip-reset	
ctuator Position Designation:	
pole two	
ip Delay Time In Seconds Per Rated Continuo	us Current:
.000 at 200 pct all locations and 45.000 at 200 p	oct all locations
closure Protection Type For Which Designed:	
ingus resistant	
ip Release Ambient Tempurature Rating:	
0.0 degrees celsius all locations	
equency In Hertz:	
0.0 all locations	
rminal Type And Quantity:	
compression	
nelf Life:	
a	
nit Of Measure:	
emilitarization:	
)	
ig:	
)30a0	