NSN 5925-00-985-8276

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-985-8276

Body Style:
Multipole-single actuator type
Bushing Length:
0.250 inches
Body Length:
1.300 inches
Body Width:
2.063 inches
Body Height:
1.875 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.750 inches
Center To Center Distance Between Terminals Parallel To Width:
0.688 inches
Pole Quantity:
3
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 threaded bushing
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
2.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
120.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
300.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
138.0 all locations
Reset Method:

Manual

NSN 5925-00-985-8276Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.469 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
5.000 at 200 pct all locations and 20.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Shockproof and vibrationproof
Trip Release Ambient Tempurature Rating:
125.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
154.0 grams
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0