

View Online at <https://aerobasegroup.com/nsn/5925-00-988-5474>

**Body Style:**

Multipole-single actuator type

**Body Length:**

10.000 inches

**Body Width:**

5.000 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

8.750 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.675 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

8.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.675 inches

**Boss Height:**

0.188 inches

**Mounting Surface To Terminal End Distance:**

7.485 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes ac all locations and 50.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac all locations and 10000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Test Data Document:**

98453-5222247 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0