

View Online at <https://aerobasegroup.com/nsn/5925-00-989-4712>

Body Style:

Single pole type

Body Length:

Between 3.480 inches and 3.520 inches

Body Width:

Between 0.940 inches and 0.980 inches

Body Height:

Between 3.040 inches and 3.080 inches

Case Material:

Plastic

Switch Contact Arrangement:

Single pole, double throw

Boss Height:

Between 0.178 inches and 0.198 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 terminal

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location and 5.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

300.0 ac single location and 125.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 ac single location and 1500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

Switch Location And Position Designation:

External at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct single location and 210.000 at 200 pct single location

Trip Release Ambient Temperature Rating:

50.0 degrees celsius single location

Switch Terminal Type:

Turret

Switch Current Rating And Type In Amps:

5.0 ac and 5.0 dc

Switch Voltage Rating And Type In Volts:

250.0 ac and 30.0 dc

Frequency In Hertz:

400.0 single location

Terminal Type And Quantity:

1 solder stud and 1 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0