

View Online at <https://aerobasegroup.com/nsn/5925-00-989-9633>

Body Style:

Single pole type

Mounting Slot Width:

0.164 inches

Body Length:

3.219 inches

Body Width:

1.469 inches

Body Height:

2.656 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

2.375 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.375 inches

Boss Height:

0.125 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded hole and 1 unthreaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

150.0 milliamperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

1.550 single location and 7.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.350 at 200 pct single location and 1.000 at 200 pct single location

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0