

View Online at <https://aerobasegroup.com/nsn/5925-00-993-0367>

Overall Length:

0.750 inches

Overall Height:

2.190 inches

Overall Width:

0.560 inches

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

Thd bushing

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location and 10.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3500.0 ac single location and 6000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

200.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Trip Delay Time In Seconds Per Rated Continuous Current:

0.200 at 200 pct single location and 0.700 at 200 pct single location

Inclosure Protection Type For Which Designed:

Dustproof and explosion proof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0