

View Online at <https://aerobasegroup.com/nsn/5925-00-993-0374>

Body Style:

Rectangular dimensional envelope

Overall Length:

4.230 inches

Overall Height:

3.700 inches

Overall Width:

0.970 inches

Case Material:

Plastic

Pole Quantity:

1

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location and 10.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

300.0 ac single location and 150.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 ac single location and 2500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

0.600 at 150 pct single location and 4.300 at 150 pct single location and 0.210 at 200 pct single location and 0.580 at 200 pct single location and 0.700 at 300 pct single location and 0.190 at 300 pct single location

Inclosure Protection Type For Which Designed:

Explosion proof

Trip Release Ambient Temperature Rating:

50.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0