NSN 5925-00-994-0405

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-994-0405

View Online at https://aerobasegroup.com/nsn/5925-00-994-0405
Body Style:
Single pole type
Bushing Length:
0.290 inches
Body Length:
1.750 inches
Body Width:
0.625 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.240 inches
Mounting Surface To Terminal End Distance:
1.638 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
Thd bushing
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
5.0 amperes dc single location
5.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts:
Operating Voltage Type And Rating Per Pole In Volts:
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2500.0 dc single location
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2500.0 dc single location Circuit Protection Type:
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2500.0 dc single location Circuit Protection Type: Overcurrent single location
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method:
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic single location
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic single location Trip Release Characteristic:
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic single location Trip Release Characteristic: Instantaneous single location
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic single location Trip Release Characteristic: Instantaneous single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic single location Trip Release Characteristic: Instantaneous single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 135.0 single location
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic single location Trip Release Characteristic: Instantaneous single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 135.0 single location Ultimate Trip Time Per Pole In Seconds:
Operating Voltage Type And Rating Per Pole In Volts:32.0 dc single locationMaximum Interrupting Capacity Current Type And Rating Per Pole In Amps:2500.0 dc single locationCircuit Protection Type:Overcurrent single locationTrip Release Method:Magnetic single locationTrip Release Characteristic:Instantaneous single locationUltimate Trip Rating Of Continuous Current Rating Per Pole In Percent:135.0 single locationUltimate Trip Time Per Pole In Seconds:0.100 single location
Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic single location Trip Release Characteristic: Instantaneous single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 135.0 single location Ultimate Trip Time Per Pole In Seconds: 0.100 single location
Operating Voltage Type And Rating Per Pole In Volts:32.0 dc single locationMaximum Interrupting Capacity Current Type And Rating Per Pole In Amps:2500.0 dc single locationCircuit Protection Type:Overcurrent single locationTrip Release Method:Magnetic single locationTrip Release Characteristic:Instantaneous single locationUltimate Trip Rating Of Continuous Current Rating Per Pole In Percent:135.0 single locationUltimate Trip Time Per Pole In Seconds:0.100 single locationReset Method:Manual

1 push button

NSN 5925-00-994-0405 Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.469 inches
Inclosure Protection Type For Which Designed:
Fungus resistant
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0