## NSN 5925-00-994-5965

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-994-5965

#### Body Style:

Rectangular dimensional envelope

**Overall Length:** 

10.000 inches

## **Overall Height:**

4.062 inches

**Overall Width:** 

5.000 inches

#### **Unthreaded Mounting Hole Diameter:**

0.201 inches

Pole Quantity:

3

#### Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

#### Maximum Continuous Load Current Rating Per Pole:

75.0 amperes ac all locations and 75.0 amperes dc all locations

## Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations and 250.0 dc all locations

#### Circuit Protection Type:

Overcurrent all locations

#### **Trip Release Method:**

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

#### Manual Actuator Type And Quantity:

1 toggle

#### **Actuator Function:**

Trip-reset

#### **Actuator Position Designation:**

At pole two

#### Trip Delay Time In Seconds Per Rated Continuous Current:

360.000 at 300 pct all locations

## Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

## Frequency In Hertz:

400.0 all locations

#### **Terminal Type And Quantity:**

6 compression

# NSN 5925-00-994-5965

Circuit Breaker Tripper - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0

