NSN 5925-00-994-6602



Circuit Breaker - Page 1 of 3 View Online at https://aerobasegroup.com/nsn/5925-00-994-6602 **Body Style:** Single pole type **Overall Length:** 1.344 inches **Overall Width:** 0.993 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.656 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.000 inches **Switch Contact Arrangement:** Single pole, double throw **Boss Height:** 0.125 inches **Mounting Surface To Terminal End Distance:** 1.875 inches **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac single location and 5.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac single location and 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 200.0 ac single location and 300.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

NSN 5925-00-994-6602 Circuit Breaker - Page 2 of 3



| Reset Method: |
|---|
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |
| 1 push-pull |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At pole one |
| Auxiliary Switch Function And Quantity: |
| 1 alarm |
| Internal Trip Release Configuration: |
| Series trip single location |
| Thread Size: |
| 0.138 inches |
| Switch Location And Position Designation: |
| Internal at pole one |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 15.000 at 200 pct single location and 30.000 at 200 pct single location |
| Inclosure Protection Type For Which Designed: |
| Fungus resistant |
| Trip Release Ambient Tempurature Rating: |
| 25.0 degrees celsius single location |
| Switch Terminal Type: |
| Pin |
| Switch Current Rating And Type In Amps: |
| 3.0 ac and 1.0 dc |
| Switch Voltage Rating And Type In Volts: |
| 120.0 ac and 50.0 dc |
| Frequency In Hertz: |
| 400.0 single location |
| Unpackaged Unit Weight: |
| 3.000 ounces |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 2 screw base |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5925-00-994-6602

Circuit Breaker - Page 3 of 3



Fiig:

A030a0