## NSN 5925-00-995-0857

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-995-0857 **Body Style:** Multipole-single actuator type **Body Length:** 6.250 inches **Body Width:** 2.230 inches **Body Height:** 2.650 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** Between 0.738 inches and 0.748 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.220 inches **Pole Quantity: Mounting Facility Type And Quantity:** 6 terminal **Storage Type:** General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 135.0 all locations **Reset Method:** Manual

**Main Contact Tripping Mechanism Type:** 

Trip free

## **NSN 5925-00-995-0857** Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
5.000 at 200 pct all locations
nclosure Protection Type For Which Designed:
Corrosion resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Special Features:
To make this cb compatible to the substitute cb you must add either p/n pk1mb, 5925-01-429-4530; and/or p/n sk5669, 5925-01-429-4529
Frequency In Hertz:
60.0 all locations
Test Data Document:
31348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 clip and 3 compression
Specification Data:
31348-w-c-375/4 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4030a0