

View Online at <https://aerobasegroup.com/nsn/5925-00-995-1631>

Thread Pitch Diameters:

+0.3503/+0.3537 inches

Body Style:

Multipole-single actuator type

Bushing Length:

0.375 inches

Body Length:

1.495 inches

Body Width:

1.872 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.678 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

6.0 amperes ac first location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Ultimate Trip Time Per Pole In Seconds:

0.700 all locations and 6.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.500 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0